

**QMTS2.E123995**
**Polymeric Materials - Filament-wound Tubing, Industrial Laminates, Vulcanized Fiber, and Materials for Use in Fabricating Recognized Printed Wiring Boards - Component**

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

**Polymeric Materials - Filament-wound Tubing, Industrial Laminates, Vulcanized Fiber, and Materials for Use in Fabricating Recognized Printed Wiring Boards - Component**

See General Information for Polymeric Materials - Filament-wound Tubing, Industrial Laminates, Vulcanized Fiber, and Materials for Use in Fabricating Recognized Printed Wiring Boards - Component

**KINGBOARD LAMINATES HOLDINGS LTD**

E123995

2ND FL, HARBOUR VIEW 1  
 NO 12 SCIENCE PARK EAST AVE  
 PHASE II, HONG KONG SCIENCE PARK  
 SHATIN, N T HONG KONG

**Industrial laminates:**

Mtl Dsg	ANSI Type	Color	Build up Min Thk (mm)	Flame Class	R.T.I.		H W I	H A I	V T R	C T I	Meets 746E Non-HAL	Meets 746E DSR
					Elec (°C)	Mech (°C)						
<b>Industrial laminates, furnished as sheets.</b>												
<b>KB-150</b>	XPC	NC, BK	0.71	HB	130	130	2	0	0	-	-	Yes
			1.57	HB	130	130	1	0	1	4	-	Yes
<b>KB-2150</b>	FR-2	NC	1.45	V-0	105	105	4	3	1	4	-	Yes
<b>KB-2150G</b>	FR-2	TN	0.71	V-0	75	75	0	3	6	-	-	Yes
			1.45	V-0	105	105	0	3	6	3	-	Yes
<b>KB-2150GC</b>	FR-2	TN	0.71	V-0	75	75	0	4	6	-	-	-
			1.45	V-0	105	105	0	3	6	0	-	Yes
<b>KB-3151S (with Adhesive)</b>												
	FR-1	NC	1.45	V-0	130	130	0	0	-	0	-	Yes
			0.71	V-0	130	130	0	0	-	-	-	Yes
<b>KB-3151S (without Adhesive)</b>												
	FR-1	NC	1.45	V-0	130	130	3	3	4	4	-	Yes
			0.71	V-0	130	130	3	3	4	-	-	Yes
<b>KB-3152</b>	FR-1	NC	0.71	V-0	130	130	0	0	-	-	-	Yes
			1.45	V-0	130	130	0	0	-	0	-	Yes
<b>KB-5150</b>	CEM-1	NC	0.63	V-0	130	140	3	2	4	-	-	Yes
			1.40	V-0	130	140	1	2	4	3	-	Yes
<b>KB-5150&amp;</b>												
	CEM-1	NC	0.63	V-0	130	140	1	3	4	-	-	Yes

			1.40	V-0	130	140	1	3	4	0	-	Yes
<b>KB-5252</b>	CEM-1	NC	0.63	V-0	130	140	3	2	-	-	-	Yes
			1.40	V-0	130	140	1	2	-	3	-	Yes
<b>KB-6150C</b>	FR-4.0	NC	0.63	V-0	130	140	0	3	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	0	-	Yes
<b>KB-6160A</b>	FR-4.0	YL	0.38	V-0	130	130	0	0	-	-	-	Yes
			0.63	V-0	130	140	0	3	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	3	-	Yes
<b>KB-6160C</b>	FR-4.0	NC	0.38	V-0	130	130	0	0	-	-	-	Yes
			0.63	V-0	130	140	0	3	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	0	-	Yes
<b>KB-6165</b>	FR-4.0	YL	0.38	V-0	130	130	2	0	-	-	-	Yes
			0.63	V-0	130	140	0	3	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	3	-	Yes
<b>KB-6168</b>	FR-4.0	NC	0.38	V-0	130	130	0	3	-	-	-	Yes
			0.63	V-0	130	140	0	3	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	3	-	Yes
<b>KB-7150</b>	CEM-3	NC	0.63	V-0	130	140	0	2	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	3	-	Yes
<b>KB-7150C</b>	CEM-3	NC	0.63	V-0	130	140	0	2	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	0	-	Yes
<b>Industrial laminates, furnished as sheets or rolls.</b>												
<b>KB-5150A</b>	CEM-1	NC	0.63	V-0	130	140	3	2	4	-	-	Yes
			1.40	V-0	130	140	1	2	4	2	-	Yes
<b>KB-5150G</b>	CEM-1	NC	0.63	V-0	130	140	3	2	4	-	-	Yes
			1.40	V-0	130	140	1	2	4	0	-	Yes
<b>KB-5150H</b>	CEM-1	NC	0.63	V-0	130	140	3	2	4	-	-	Yes
			1.40	V-0	130	140	1	2	4	2	-	Yes
<b>KB-5150L</b>	CEM-1	NC	0.63	V-0	130	140	3	2	4	-	-	Yes
			1.40	V-0	130	140	1	2	4	3	-	Yes
<b>KB-616(X)</b>	FR-4.0	YL	0.38	V-0	130	130	3	3	-	-	-	Yes
			0.63	V-0	130	140	0	3	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	3	-	Yes
<b>KB-6164F</b>	FR-4.0	NC	0.38	V-0	130	130	0	4	-	-	-	-
			0.63	V-0	130	140	0	2	-	-	-	Yes
			1.40	V-0	130	140	0	1	-	3	-	Yes
<b>KB-6165F</b>	FR-4.0	NC(YL)	0.38	V-0	130	130	3	3	-	-	-	Yes
			0.63	V-0	130	140	0	3	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	3	-	Yes
<b>KB-6165G</b>	FR-4.1	NC	0.05	V-0	120	100	0	3	-	-	Yes	Yes
			0.38	V-0	130	130	0	1	-	-	-	Yes
			0.63	V-0	130	140	0	1	-	-	-	Yes

			1.40	V-0	130	140	0	1	-	3	-	Yes
<b>KB-6165GC</b>	FR-4.1	NC	0.05	V-0	120	100	0	3	-	-	Yes	Yes
			0.38	V-0	130	130	0	1	-	-	-	Yes
			0.63	V-0	130	140	0	1	-	-	-	Yes
			1.40	V-0	130	140	0	1	-	0	-	Yes
<b>KB-6167A</b>	FR-4.0	NC	0.38	V-0	130	130	0	2	-	-	-	Yes
			0.63	V-0	130	140	0	2	4	-	-	Yes
			1.40	V-0	130	140	0	1	4	4	-	Yes
<b>KB-6167F</b>	FR-4.0	NC	0.38	V-0	130	130	0	3	-	-	-	Yes
			0.63	V-0	130	140	0	3	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	3	-	Yes
<b>KB-6167G</b>	FR-4.1	NC	0.05	V-0	120	100	0	3	-	-	Yes	Yes
			0.38	V-0	130	130	0	1	-	-	-	Yes
			0.63	V-0	130	140	0	1	-	-	-	Yes
			1.40	V-0	130	140	0	1	-	0	-	Yes
<b>KB-6167GMD</b>												
	FR-4.1	NC	0.38	V-0	130	130	0	1	-	-	Yes	Yes
			0.63	V-0	130	140	0	1	-	-	-	Yes
			1.40	V-0	130	140	0	0	-	0	-	Yes
<b>KB-7150T</b>	CEM-3	NC	0.63	V-0	130	140	0	2	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	0	-	Yes
<b>Industrial laminates, furnished as sheets, rods or tubes.</b>												
<b>HF-140</b>	FR-4.1	NC	0.38	V-0	130	130	0	2	-	-	Yes	Yes
			0.63	V-0	130	140	0	2	-	-	-	Yes
			1.40	V-0	130	140	0	2	-	3	-	Yes
<b>KB-3150N</b>	FR-1	NC	0.71	V-0	130	130	0	0	-	-	-	Yes
			1.45	V-0	130	130	-	-	-	3	-	Yes
<b>KB-3150NU %</b>												
	FR-1	NC	0.71	V-0	130	130	3	3	4	-	-	Yes
			1.45	V-0	130	130	3	3	4	4	-	Yes
<b>KB-3151HS</b>	FR-1	NC	0.71	V-0	130	130	0	0	4	-	-	Yes
			1.45	V-0	130	130	0	0	4	0	-	Yes
<b>KB-3152C</b>	FR-1	NC	0.71	V-0	130	130	0	0	4	-	-	Yes
			1.45	V-0	130	130	0	0	4	0	-	Yes
<b>KB-3152S</b>	FR-1	NC	0.71	V-0	130	130	0	0	4	-	-	Yes
			1.45	V-0	130	130	0	0	4	0	-	Yes
<b>KB-3153*</b>	FR-1	NC	0.71	V-0	130	130	0	0	4	-	-	Yes
			1.45	V-0	130	130	0	0	4	0	-	Yes
<b>KB-5152</b>	No ANSI	NC	0.60	V-0	-	-	-	-	-	-	-	-
<b>KB-6150</b>	FR-4.0	NC	0.10	V-0	120	125	0	3	-	-	-	Yes
			0.63	V-0	130	140	0	3	4	-	-	Yes
			1.40	V-0	130	140	0	2	4	4	-	Yes









	KB-6165G	-	FR-4.1	0.05	17	102	-	50.8	V-0	100	288	20
				0.38	17	102	-	50.8	V-0	130	288	20
<b>KB-6165GC</b>												
	KB-6165GC	-	FR-4.1	0.05	17	102	-	50.8	V-0	100	288	20
				0.38	17	102	-	50.8	V-0	130	288	20
<b>KB-6167A</b>												
	KB-6167A	-	FR-4.0	0.38	17	102	-	50.8	V-0	130	288	30
<b>KB-6167F</b>												
	KB-6167F	-	FR-4.0	0.38	12	102	-	50.8	V-0	130	288	60
<b>KB-6167G</b>												
	KB-6167G	-	FR-4.1	0.05	17	102	-	50.8	V-0	100	288	20
				0.38	17	102	-	50.8	V-0	130	288	20
<b>KB-6168</b>												
	KB-6168	-	FR-4.0	0.38	12	102	-	50.8	V-0	130	288	60
<b>KB-7150</b>												
	KB-7150	-	CEM-3	0.63	17	102	-	50.8	V-0	130	290	20
<b>KB-7150C</b>												
	KB-7150C	-	CEM-3	0.63	17	102	-	50.8	V-0	130	288	20
<b>KB-7150T</b>												
	KB-7150T	-	CEM-3	0.63	17	102	-	50.8	V-0	130	288	20
<b>Metal clad industrial laminates for use in single layer printed wiring boards with copper on one or both sides, furnished as sheets, rods or tubes.</b>												
<b>HF-140</b>												
	HF-140	-	FR-4.1	0.38	12	102	-	50.8	V-0	130	288	30
<b>KB-3152C</b>												
	KB-3152C	-	FR-1	0.71	34	102	-	50.8	V-0	130	260	10
<b>KB-3152S</b>												
	KB-3152S	-	FR-1	0.71	34	102	-	50.8	V-0	130	260	10
<b>KB-3153*</b>												
	KB-3153	-	FR-1	0.71	34	102	-	50.8	V-0	130	260	10
<b>KB-6167GLD,KB-6165GMD,KB-6165GLD,KB-6167GMD</b>												
	KB-6167GLD, KB-6165GMD, KB-6165GLD, KB-6167GMD	-	FR-4.1	0.38	12	102	-	50.8	V-0	130	288	30
<b>Metal clad industrial laminates for use in single layer printed wiring boards with copper on one or both sides.</b>												



<b>EEL-128</b>												
	EEL-128	-	FR-4.0	0.38	17	102	-	38.1	V-0	130	288	30
				0.63	17	102	-	50.8	V-0	130	288	30
<b>EEL-145</b>												
	EEL-145	-	FR-4.0	0.38	17	102	-	50.8	V-0	130	288	30
<b>KB-3151C*</b>												
	KB-3151C	-	FR-1	0.71	17	102	-	50.8	V-0	130	260	10
<b>KB-3151S</b>												
	KB-3151S	-	FR-1	0.71	17	102	-	38.1	V-0	130	260	10
<b>KB-5150A</b>												
	KB-5150A	-	CEM-1	0.63	17	102	-	50.8	V-0	130	288	20
<b>KB-5150H</b>												
	KB-5150H	-	CEM-1	0.63	17	102	-	50.8	V-0	130	288	20
<b>KB-5150L</b>												
	KB-5150L	-	CEM-1	0.63	17	102	-	50.8	V-0	130	260	10
<b>KB-6155</b>												
	KB-6155	-	FR-4.0	0.38	12	102	-	50.8	V-0	130	288	60
<b>KB-7152</b>												
	KB-7152	-	CEM-3	0.63	17	102	-	50.8	V-0	130	288	20
<b>Metal clad industrial laminates for use in single layer printed wiring boards with copper on one side only, furnished as sheets.</b>												
<b>KB-1150</b>												
	KB-150	-	XPC	0.71	35	117	-	25.4	HB	130	260	10
<b>KB-5150</b>												
	KB-5150	-	CEM-1	0.71	35	102	-	50.8	V-0	130	260	10
<b>KB-5150G</b>												
	KB-5150G	-	CEM-1	0.63	17	102	-	50.8	V-0	130	288	10
<b>KB-5252</b>												
	KB-5252	-	CEM-1	0.63	17	102	-	50.8	V-0	130	288	10
<b>Metal clad industrial laminates for use in single layer printed wiring boards with copper on one side only, furnished as sheets, rods or tubes.</b>												
<b>KB-3150N</b>												
	KB-3150NU %	-	FR-1	0.71	17	102	-	50.8	V-0	130	260	10
<b>KB-3151HS</b>												
	KB-3151HS	-	FR-1	0.71	34	102	-	50.8	V-0	130	260	10

**Metal clad industrial laminates for use in multilayer printed wiring boards with copper on one or both sides.**

**KB-6155**

	KB-6155	KB-6055	FR-4.0	0.38	12	102	70	50.8	V-0	130	288	60
--	---------	---------	--------	------	----	-----	----	------	-----	-----	-----	----

**Metal clad industrial laminates (Flammability Only Recognition):**

				Bld up	Clad Cond Thk			Max		Max	Solder Lts	
Metal Clad Dsg	Lam-inate Dsg	Pre-preg Dsg	ANSI Type	Min Thk (mm)	Min Ext (mic)	Max Ext (mic)	Max Int (mic)	Area Dia (mm)	Flame Class	Oper Temp (°C)	Temp (°C)	Time (sec)
<b>Metal clad industrial laminates for use in single layer printed wiring boards with copper on one or both sides, furnished as sheets (Flammability Only Recognition).</b>												
<b>KB-5152</b>												
	KB-5152	-	No ANSI	0.60	-	-	-	-	V-0	-	260	10
<b>KB-6162</b>												
	KB-6162	-	No ANSI	0.63	-	-	-	-	V-0	-	288	30

% - Corresponds to Unclad values without adhesive. For declad values (single sided) see corresponding grade "KB-3150N"

& - Corresponds to Declad values with adhesive. For Unclad values see corresponding grade designation.

\* - With adhesive

X - may be 0, 4

Marking: Company name and material designation on container or wrapper.

Last Updated on 2016-06-28

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".